



DESCRIPTION

The **CBS ArcSafe® RRS-3 Compact NS** allows technicians to remotely rack in or out all type Compact NS low-voltage power circuit breakers from a safe distance while remaining stationed outside the arc-flash boundary. The CBS ArcSafe RRS-3 Compact NS is compatible with all Merlin-Gerin/Schneider electrically operated Compact NS breakers housed within the withdrawable circuit breaker chassis. Installation and operation of the CBS ArcSafe RRS-3 Compact NS is quick, simple, and does not require any modifications to the existing equipment. Typical applications of the Compact NS circuit breakers include petrochemical plants, oil platforms, hospitals, data centers, and industrial facilities. By automating the racking procedure, the CBS ArcSafe RRS-3 Compact NS reduces operator fatigue and increases operator safety.

SPECIFICATIONS

WEIGHT:	16 lbs
DIMENSIONS:	19.8"H x 10.9"W x 17.7"D
POWER CONSUMPTION:	50W
OPERATING DISTANCE:	25-300 feet
COMPATIBILITY:	Compact NS (electrically operated, housed within withdrawable circuit breaker chassis)
CONTROL/POWER SOURCE:	CBS ArcSafe® RSO-IV Control Console

OVERVIEW

- Remote operation from up to 300 feet away
- Lightweight and portable for hard-to-access areas
- Simple setup, no equipment modification required
- Quick installation and removal from gear
- Adjustable travel and locators to accommodate entire product line
- Reduces or eliminates need for arc-flash hazard suits
- Eliminates all hazardous manual contact with gear during operation
- Designed, manufactured, and assembled in the USA

