



DESCRIPTION

The CBS ArcSafe® RRS-3 DS allows technicians to remotely rack IN or OUT the DS style low voltage power circuit breaker from a safe distance while remaining stationed outside of the arc-flash boundary. Installation and operation of the CBS ArcSafe® RRS-3 DS is quick and simple and does not require any modifications to the existing equipment. The CBS ArcSafe® RRS-3 DS is compatible with all DS style circuit breakers manufactured by Westinghouse, Cutler-Hammer, and Eaton with current ratings from 800-5000A. The DS style circuit breakers may typically be found in generation, chiller/HVAC, petrochemical, water/waste treatment, pulp/paper, and data center applications. By automating the racking procedure, the CBS ArcSafe® RRS-3 DS reduces operator fatigue and increases operator safety.

SPECIFICATIONS

WEIGHT:	18.5 pounds
DIMENSIONS:	13.0" T x 9.3" W x 9.5" D
POWER CONSUMPTION:	100 Watts
OPERATING DISTANCE:	25-300 feet
COMPATIBILITY:	All DS/DSL/DSII/DSLII-206/206S/416/416S/420/632/840 Low Voltage Power Circuit Breakers
CONTROL/POWER SOURCE:	CBS ArcSafe® RSO-IV control console



BENEFITS

- Remote operation from up to 300 feet away
- Lightweight and portable for hard-to-access areas
- Simple setup, no equipment modification required
- Quick installation and removal from gear
- Adjustable travel and locators to accommodate entire product line
- Reduces or eliminates need for arc-flash hazard suits
- Eliminates all hazardous manual contact with gear during operation
- Designed, manufactured, and assembled in the USA

