

Remote Switching Kit (RSK) compatible with most dual-pushbutton applications & standard breaker control switches

Patent Pending*

DESCRIPTION

The CBS ArcSafe® **RSK-CSH-W** is a wireless remote switching kit (RSK) designed to safely operate most single & dual pushbutton applications requiring less than 10 lbs. of push force and spaced 3.00" or less center-to-center, as well as breaker control switches with pistol-grip handles such as the Electroswitch Series 24/24P and GE SB-1.



Operating from up to 100 feet away, the RSK-CSH-W keeps the operator well outside the arc flash boundary. The unit magnetically attaches to switchgear so that no modifications or downtime is required.

A motorized actuator and dual-adjustable linear actuators precisely operate switches and pushbuttons, while an on-board microcontroller ensures accurate positioning and reliable performance.

Each RSK-CSH-W includes the actuator assembly, power/communications base, wireless handheld controller (100-ft range), M18™ REDLITHIUM™ rechargeable battery, battery charger, durable waterproof case, and instruction manual.

PUSHBUTTON APPLICATIONS

The **RSK-CSH-W** offers extensive adjustability to accommodate a wide range of ICCB, ACB, VCB, and other single or dual pushbutton applications found in the field today. With its **adjustable actuator system and onboard laser alignment** for precise positioning, users can confidently operate equipment from multiple OEMs and configurations using a single versatile tool.



Actuator adjustability shown above from 1.125" up to 3.00" from center-to-center of the intended pushbuttons via the red handheld knobs on the side of the assembly.

POWERED BY
M18 REDLITHIUM

CS*
CHICKEN
SWITCH®

Distance is Safety®
CBSArcSafe.com

(472-3389)
(877) 4-SAFETY



2616 SIRIUS ROAD, DENTON, TX 76208 | INFO@CBSARCSAFE.COM

RSK-CSH-W

Chicken Switch Hitter

Remote Switching Kit (RSK) compatible with most dual-pushbutton applications & standard breaker control switches


Patent Pending*

BATTERY BASE & COMMUNICATION SPECIFICATIONS


- Power supply: POWERED BY M18™ REDLITHIUM™ CP2.0 (Milwaukee part no. 48-11-1820); other M18 batteries are compatible. *Note: Use only batteries manufactured by Milwaukee; otherwise warranty will be void.*
- Wireless transmitter information:
Operating frequency: ISM 2.4 Ghz
Line of sight range: 150 ft.
Encryption: 128/256 bit AES
Interference Immunity: DSSS
Transmitter Power: (2) AA Batteries
- Motor & Actuator Assembly weight: 8 lbs.
- Motor & Actuator Assembly size: 9.5" x 10" x 5.5" (L,W,H)
- Battery/Communication Base weight: 3.75 lbs.
- Battery/Communication Base size: 5" x 5.5" x 5.25" (L,W,H)

Battery base selections include:

- WAKE & SLEEP functions as standard on RSK-CS equipment
- Motor travel selection of 45° or 90°
- Control switch or pushbutton output selection



APPLICATION PHOTOS



Distance is Safety®
CBSArcSafe.com

(472-3389)
(877) 4-SAFETY



2616 SIRIUS ROAD, DENTON, TX 76208 | INFO@CBSARCSAFE.COM